

Innovation
for a Better Life



CHANGE YOUR ENERGY CHARGE YOUR LIFE



RESU



Compact Size & Easy Installation

The compact and lightweight nature of the RESU is world-class. It is designed to allow easy wall-mounted or floor-standing installation for both indoor and outdoor applications. The inverter connections have also been simplified, reducing installation time and costs.



Powerful Performance

The new RESU series features industry-leading continuous power (4.2kW for RESU6.5) and DC round-trip efficiency (95%). LG Chem's L&S (Lamination & Stacking) technology provides durability ensuring 80% of capacity retention after 10 years.



Proven Safety

LG Chem places the highest priority on safety and utilizes the same technology for its ESS products that has a proven safety record in its automotive battery. All products are fully certified in relevant global standards.

48V



Models		RESU3.3	RESU6.5	RESU10
Total Energy [kWh]		3.3	6.5	9.8
Usable Energy [kWh]		2.9	5.9	8.8
Capacity [Ah]		63	126	189
Nominal Voltage [V]		51.8	51.8	51.8
Voltage Range [V]		42.0-58.8	42.0-58.8	42.0-58.8
Max Power [kW]		3.0	4.2	5.0
Peak Power [kW] (for 3 sec.)		3.3	4.6	7.0
Dimension [W x H x D, mm]		452 x 401 x 120	452 x 654 x 120	452 x 483 x 227
Weight [kg]		31	52	75
Enclosure Protection Rating		IP55		
Communication		CAN 2.0 B		
Certificates	Cell	UL1642		
	Product	CE / RCM / TUV (IEC 62619) / UL1973		

Compatible Inverter Brands : SMA, SolaX, Sungrow, Schneider, Ingeteam, GoodWe, Redback, Victron Energy (As of 3Q. 2016, More brands to be added)

RESU PLUS



RESU Plus is an expansion kit specially designed for 48V models of new RESU series. With RESU Plus, all 48V models can be cross-connected with each other.

- Dimension: 385 x 240 x 65 (W x H x D, mm)
- Number of Expandable Battery Units: Up to 2EA
- IP55

400V



Models		RESU7H	RESU10H	
Total Energy [kWh]		7.0	9.8	
Usable Energy [kWh]		6.6	9.3	
Capacity [Ah]		63	63	
Voltage Range [V]		350-450	350-450	385-550
Max Power [kW]		3.5	5.0	
Peak Power [kW] (for 10 sec.)		5.0	7.0	
Dimension [W x H x D, mm]		744 x 692 x 206	744 x 907 x 206	
Weight [kg]		76	97	99.8
Enclosure Protection Rating		IP55		
Communication		RS485	RS485	CAN 2.0 B
Certificates	Cell	UL 1642		
	Product	TUV (IEC 62619) / CE	TUV (IEC 62619) / UL1973 / CE	

Compatible Inverter Brands : SMA, SolarEdge (As of 3Q. 2016, More brands to be added)